

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 05004501
PUBLICATION DATE : 14-01-93


APPLICATION DATE : 01-02-91
APPLICATION NUMBER : 03033479

APPLICANT : ASAHI TEC CORP;

INVENTOR : OTOMO MAKOTO;

INT.CL. : B60B 1/08 B60B 3/06

TITLE : WHEEL FOR VEHICLE



ABSTRACT : **PURPOSE:** To judge various kinds of information on a cast wheel through a process of reading a bar code before a post-treatment work so that the information may be utilized for a corresponding treatment by forming a bar code formed by projections extending over at least one-third the whole periphery of a rim in the circumferential direction on the surface of the rim.

CONSTITUTION: An axle hole 11 is formed in the disc portion 1 of a cast wheel W. A rim portion 2 is integrally formed on the outer peripheral edge of the disc portion 1. In this case, plural projections 3 are formed in parallel in the circumferential direction, on the outer surface of the rim portion 2 extending over at least one third the whole periphery thereof by casting. A bar code is formed by the respective projections 3 to represent various kinds of information (rim system, rim width and the like) on the cast wheel W. On the other hand, various kinds of information are read by a detector not shown to be utilized for a corresponding treatment. The cast wheel W is formed into a designated shape by a lathe in a finishing process, and the projections 3 as a bar code are erased from the final product of a wheel for a vehicle.

COPYRIGHT: (C)1993,JPO&Japio

(19) 日本国特許庁 (J P)

(12) 公開特許公報 (A)

(11) 特許出願公開番号

特開平5-4501

(43) 公開日 平成5年(1993)1月14日

(51) Int.Cl. ⁵	識別記号	弁内整理番号	F I	技術表示箇所
B 6 0 B	1/08	7146-3D		
	3/06	7146-3D		

審査請求 未請求 請求項の数 3 (全 3 頁)

(21) 出願番号 特願平3-33479

(22) 出願日 平成3年(1991)2月1日

(71) 出願人 000116873

旭テック株式会社

静岡県小笠郡菊川町堀之内547番地の1

(72) 発明者 大友 誠

静岡県小笠郡小笠町菊川町加茂3883番地の
2


(74) 代理人 弁理士 野末 祐司

(54) 【発明の名称】 車両用ホイール

(57) 【要約】

【構成】 リムの表面の周方向に、少なくとも全周の三分の一以上の長さのバーコードを形成したもの。


【効果】 車両用ホイールの固有の情報（例えばリム径、リム幅またはボルト孔のピッチ等）をバーコードにより判読することができる。



(3)

特開平 5-4501

【図1】



【図2】

